



Precision-V AE-1400 Vapor Degreaser Solvent Product# 1681

Product Description

Techspray® has engineered solvent cleaners that offer exciting new options for precision cleaning. Precision-V cleaners are powerful, leave no residue, evaporate extremely fast, and are nonflammable with no flash-point. Electronics, optics, and metal parts are quickly and thoroughly cleaned, eliminating the need for further rinsing. Precision-V is non-ozone depleting, so ideal replacements for cleaners containing Freon, HFC-141b and AK225.

Precision-V AE-1400 has azeotropic properties that allow it to remain stable as it is cycled in a vapor degreaser. It is neither reactive nor corrosive to metals commonly found in the construction of vapor degreasers. It is also safe for most materials found in circuit board manufacturing.

NOTE: As with all vapor degreaser equipment and processes, observe all safety precautions, guidelines and operating rules associated with these units. Failure to do so may put operations personnel at risk. Avoid excessive vapor losses, loss of refrigeration, excessive boil sump heat, etc. Make sure all equipment is operated in accordance with the manufacturer's guidelines and instructions. If in doubt, contact your manufacturer immediately.

Ideal for...

- Removing flux residues resulting from soldering and/or PCB assembly
- Precision cleaning of metals, alloys, composites, and plastics
- Drying agent after cleaning with water solutions, hydrocarbons or alcohols
- Removal of particles and polishing media

Features / Benefits

- Nonflammable
- Excellent thermal, chemical, and hydrolytic stability
- Low surface tension, low viscosity, high liquid density
- Recyclable
- Residue-Free
- Non-ozone depleting



Typical Product Data and Physical Properties

Physical state:	Liquid
Flash Point:	Closed cup: >199.9°F (>93.3°C)
Color:	Clear, colorless
Odor:	Ethereal
Boiling/Condensation point:	128.7°F (53.7°C)
Melting/freezing point:	-130°F (-90°C)
Vapor pressure:	28 kPa (210 mmHg)
Evaporation rate:	66 (ether (anhydrous)=1)
Shelf life:	

Precision-V AE-1400 Vapor Degreaser Solvent

Product# 1681

Reclamation Process

The reclamation (ie. boil down) process utilizes the vapor-degreaser as a still to distill solvent from the dirty boil sump and allows you to reclaim and reuse this solvent.

When it is determined that the Boil Sump needs to be cleaned out, you should do the following things to boil down the solvent:

1. If you have a 2 sump vapor-degreaser, drain the rinse sump into a clean container for reuse. If you have a one-sump vapor-degreaser, drain the spray reservoir using the spray wand. This material should be collected in a clean container, so it can be reused.
2. Allow the solvent to continue to boil, and the vapors to condense, until such time as one of two things happens:
 - a. the High Temperature Control (HTC) trips and turns off the heat to the heating elements or b. the Liquid Level Control trips because the level in the Boil Sump is too low.
3. Drain the remaining solvent/soil mixture into a container that is labeled as Hazardous Waste. This material can be used in future "boil downs" to reclaim more of the solvent in the mixture.
4. Use the retained solvent (from step 1) to refill the vapor-degreaser and add whatever volume of solvent is necessary to completely fill the machine.

This process can be repeated as often as necessary, depending on the amount of usage of the vapor-degreaser and the amount of soil that is introduced into the vapor-degreaser.

When you "boil down", always put the solvent/soil mixture into the vapor-degreaser to reclaim additional amount of the solvent from this mixture.

Packaging and Availability

1681-5G	5 gallon
1681-54G	54 gallon

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.