



E-Line Degreaser

1615-16S

Introduction

Maintenance cleaners clean oil and contaminants off of solenoids, coil windings, metal parts, printed circuit boards, barcode instruments, switch boxes, gear boxes, and engines. Grease and oil flow right off, reducing the time and materials needed to scrub off stubborn soils.

E-Line Degreaser is a non-chlorinated degreaser and electrical cleaner, formulated to be powerful, yet very economical. Eliminate brushing and scrubbing, saving time and materials. This product was originally formulated for the difficult cleaning applications, and is ideal for removing oils, greases and carbon residues from control panels, switch plates, enclosures, motors, and work surfaces in manufacturing finished goods. It exhibits slower evaporation which allows the solvent to soak in and break down difficult to remove soils. Note: Not for retail sale – for manufacturing use only.

Features / Benefits

- Ideal for electrical & maintenance cleaning
- Removes encrusted dirt, silicone grease and other contaminants
- High flash point
- Completely non-chlorinated and non-brominated
- Leaves no residues
- Excellent dielectric strength
- Contains no CFCs or HCFCs
- Plastic safe, non-corrosive
- Low odor
- Low toxicity

Applications

- Cold/Bucket Cleaning
- Motor Cleaning
- Plant Maintenance
- Transit Maintenance
- Machine and Parts Maintenance

Chemical Components

Component	CAS#
Distillates (petroleum).....	64742-47-8
Carbon Dioxide.....	124-38-9

Chemical Properties (SDS available on request)

- PHYSICAL STATE: Liquid
- ODOR: Faint ethereal odor
- COLOR: Clear
- PERCENT VOLATILE: 100
- FLASHPOINT (METHOD): >199.9°F / >93.3°C (TAG CC)
- RELATIVE DENSITY: 0.79
- BOILING POINT: 424°F / 218°C
- VOC: Carb – 97%
SCAQMD – 756 g/L
EPA – 97%
- KB VALUE: 31
- DIELECTRIC BREAKDOWN: >40 kV

Material Compatibility

- ABS.....Excellent
- Buna-N.....Excellent
- EPDMGood
- GraphiteExcellent
- HDPEExcellent
- Kynar™Excellent
- LDPEExcellent
- Lexan™Excellent
- NeopreneExcellent
- Noryl®Excellent
- Nylon 66™Excellent
- Cross-Linked PEExcellent
- PolypropyleneExcellent
- PolystyreneExcellent
- PVCExcellent
- Silicone Rubber.....Good
- Teflon™Excellent
- Viton™Excellent

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

1615-16S 16 oz. Aerosol Can
12 cans/case

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Techspray
8125 Cobb Center Drive
Kennesaw, GA 30152
800-858-4043
email: tsales@techspray.com

Europe
ITW Contamination Control BV
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+45 87 400 220
email: info@itw-cc.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

Techspray is a registered trademark of ITW. Unauthorized use of the trademarks and copyrights of Techspray, without the express, written permission of Techspray, is strictly prohibited. All rights reserved.