

NYCTA CONTACT CLEANER PL64742-NYT-16S

Introduction

Maintenance cleaners clean oil and contaminants off a variety of industrial equipment including: solenoids; coil windings; metal parts; printed circuit boards; barcode instruments; switch boxes; gear boxes; and engines. Grease and oil are easily removed, reducing the time and materials needed to scrub off stubborn soils.

NYCTA Contact Cleaner is a non-chlorinated degreaser and electrical cleaner. This product was originally formulated for the difficult cleaning applications found in the NYCTA, and is ideal for removing oils, greases and carbon residues from control panels, switch plates, enclosures, motors and other work surfaces. It exhibits slower evaporation which allows the solvent to soak in and break down difficult, hard to remove soils.

Features / Benefits

- Ideal for electrical & industrial maintenance (MRO) cleaning
- Removes encrusted dirt, silicone grease and other contaminants
- High flash point
- Completely non-chlorinated and non-brominated
- Leaves no residues
- Excellent dielectric strength
- Contains no CFCs or HCFCs
- Plastic safe, non-corrosive
- Low odor
- Low toxicity

Applications

- Cold/Bucket Cleaning
- Electrical Cleaning
- Motor Cleaning
- Plant Maintenance
- Transit System Maintenance
- Machine and Parts Maintenance
- Metal Cleaning

Chemical Components

Component	CAS#
Distillates (petroleum)	
Carbon Dioxide	

Chemical Properties (SDS available on request)

- PHYSICAL STATE: Liquid
- ODOR: Faint ethereal odor
- COLOR: Clear
- PERCENT VOLATILE: 100
- FLASHPOINT (METHOD): >199.9°F / >93.3°C (TAG CC)
- RELATIVE DENSITY: 0.79
- BOILING POINT: 424°F / 218°C
- VOC: Carb 97%
 - SCAQMD 756 g/L
 - EPA 97%
- KB VALUE: 31
- DIELECTRIC BREAKDOWN: >40 kV

Material Compatibility

- ABS.....Excellent
- Buna-N....Excellent
- EPDMGood
- GraphiteExcellent
- HDPE.....Excellent
- Kynar™.....Excellent
- LDPEExcellent
- Lexan[™].....Excellent
 NeopreneExcellent
- Nylon 66[™].....Excellent
- Cross-Linked PE.....Excellent
- PolypropyleneExcellent
- PolystyreneExcellent
- PVCExcellent
- Silicone Rubber......Good
- Teflon[™]Excellent
- Viton[™].....Excellent

Environmental Policy

Techspray[®] is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

PL64742-NYT-16S

16 oz. Aerosol Can 12 cans/case

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 800-858-4043 email: tsales@techspray.com Europe ITW Contamination Control BV Saffierlaan 5 2132 VZ Hoofddorp The Netherlands +45 87 400 220 email: info@itw-cc.com **Countries Outside US** Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

Techspray is a registered trademark of ITW. Unauthorized use of the trademarks and copyrights of Techspray, without the express, written permission of Techspray, is strictly prohibited. All rights reserved.