

Precision-V Plastic-Safe Cleaner

1652

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, leadfree temperatures are more baked on and harder to clean. Techspray flux removers have been proven very effective at removing fluxes baked on at leadfree temperatures.





Non-flammable & plastic-safe high precision cleaner

PlasticSafe formula is engineered for use on sensitive plastic components, packaging and casements. Ideal for optics cleaning, critical electronics and other sensitive surfaces. Qualifies under the aerospace NESHAP VOC guidelines.

- · Ideal for sensitive plastics
- Non-flammable
- Non-ozone depleting
- Safe on electronics
- Rapid evaporation
- Zero residue
- EPA SNAP approved
- Low VOC
- · Dielectric strength 23 kv

Specifications:

- NESHAP 63.741-753
- . MIL PRF-29608A class C, type I

Product Packaging

1652-10S 1652-G

Precision-V Plastic-Safe Cleaner Precision-V Plastic-Safe Cleaner

10 oz 1 gal 12 units/case 1 units/case







Technical Information

Chemical Composition

CHEMICAL NAME	CAS#
1,2-transdichloroethylene	156-60-5
Methyl nonafluorobutyl ether	163702-07-6
Methyl nonafluoroisobutyl ether	163702-08-7
n-Heptane	142-82-5
Ethanol	64-17-5
Methanol	67-56-1
1,1,1,2-Tetrafluoroethane (aerosol)	811-97-2
Carbon dioxide (aerosol)	124-38-9

Plastics & Rubber Compatibility

MATERIAL NAME	RATING
ABS	Excellent
Nylon	Excellent
Lexan	Excellent
HDPE	Excellent
LDPE	Excellent
C. E. Phenolic	Excellent
РММА	Good - slight softening
POM	Excellent
PP	Excellent
PS	Good - slight softening & fogging
PTFE	Excellent
PVC	Good - slight softening & fogging

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.





Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray P.O. Box 949 Amarillo, TX 79105 800-858-4043

Email: tsales@techspray.com

<u>Europe</u>

ITW Contamination Control Saffierlaan 5 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 Email: info@itw-cc.com Countries Outside US

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2016 Techspray, A Division of ITW

