

February, 2016

3M™ Scotch® Filament Tape 897

Product Description

Scotch® Filament Tape 897 is a glass-filament-reinforced tape suitable for light to medium duty strapping, bundling, and reinforcing applications. Scotch® Tape 897 has a synthetic rubber adhesive with good adhesion to most fiberboard surfaces and to a variety of plastic and metal surfaces.

Product Features

- UL recognized 969 file MH26206
- Abrasion and moisture resistant.
- Allows printing and illustrations to be seen through the tape.
- Good shear and initial adhesion.
- Good aging.
- Protection of filaments and adhesive to provide longer package life.
- Maximizes package performance when exposed to outdoor and humid environments.
- Less tape needed for applications where high tensile strength is a main requirement.
- Clear display of graphics, artwork, and other important messages.
- Good holding with minimum amount of tape under wide range application conditions.
- Hold with minimum rubdown.
- Boxes remain closed for long period of time.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Backing Color	Clear		
Total Tape Thickness	0.127 mm	5 mil	ASTM D3652
Backing	Polypropylene film		
Adhesive	Pressure sensitive synthetic rubber		
Reinforcement	Glass yarn		

Typical Performance Characteristics

Peel Adhesion		
5.5 N/cm	55 N/100mm	50 oz/in

Property: Peel Adhesion
 Method: ASTM D3330
 Substrate: Stainless Steel

Tensile Strength		
297.7 N/cm	2,977 N/100mm	170 lb/in

Property: Tensile Strength
 Method: ASTM D3759

Elongation at Break: 4 %

Methods
 ASTM D3759

Handling/Application Information

Application Techniques

An extensive line of hand-held dispensers is available. Application of Scotch® Filament Tape 897 is most easily accomplished at room temperature. At lower temperatures, approaching 32°F (0°C), the adhesive becomes firm. Once applied, Scotch® Tape 897 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock. To obtain best performance, use this product within 18 months from date of manufacture.

Trademarks

Scotch is a registered trademark of 3M.
 3M is a trademark of 3M.

References

Safety Data Sheet (SDS)

https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=897

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

