

3M Scotch-Grip™ High Performance Contact Adhesive 1358

Page 1, total 2 pages

Technical data

Jan. 2008

Features

- High performance contact adhesives.
- Long bonding range.
- Excellent initial strength.
- Can be used to bond most rubber, cloth, metal, wood, foamed glass, paper honeycomb, decorative plastic laminates and many other substrates.
- High heat resistance.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Viscosity (approx.):	200-800 cps
Color:	Yellow
Solids content (by wt.):	15 - 25%
180° peel strength (Canvas/Wood):	> 15 pound/inch (24°C, 50% relative humidity, 3 days)
Package:	15 litre
Work Life:	10 – 30 minutes (24°C, 50% relative humidity, 3 days)
Shelf life:	12 months

Storage

Store product at 60-80°F (16-27°C) for maximum storage life. Higher temperatures can reduce normal storage life. Lower temperatures can cause increased viscosity of a temporary nature. Rotate stock on a “first in-first out” basis.

For Additional Information

To request additional product information or to arrange for sales assistance, please contact local 3M sales representative.

Scotch-GripTM

High Performance Contact Adhesive

1358

Page 2, total 2 pages

Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application

Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



Industrial & Transportation Business Group
3M China Limited
38/F, Maxdo Center
No. 8 Xing Yi Road Shanghai
Post Code: 200336
Telephone: +86-21 62753535
Fax: +86-21 62957736