

## VieTape RT8001

### FACESTOCK

Type: Coated paper - FSC  
 Basic Weight:  $70 \pm 3 \text{ g/m}^2$   
 Caliper:  $53 \pm 3 \mu\text{m}$

### GENERAL CHARACTERISTICS:

This product is suitable for a number of promotional and industrial labels. The facestock has been designed to give optimum performance by giving very good results with heavy ink coverage printing while still maintaining enough opacity required for the application. It adheres well to a variety of substrates. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

Suggestion: don't use on PVC or softer type of surfaces.

### ADHESIVE

Type: A global general-purpose permanent, rubber-based adhesive.

Item	Value	Note
Initial Tack Glass	530N/m (13.25N/25mm)	FTM 9 glass
Adhesion to Stainless Steel	250N/m (6.25N/25mm)	FTM 2 st.st.
Thickness	$18 \pm 2 \mu\text{m}$	
Minimum Application Temperature	0°C	
Service Temperature	-40°C to 70°C subject to facestock limitations	

### LINER

Type: White glassine paper  
 Basic Weight:  $60 \pm 3 \text{ g/m}^2$   
 Caliper:  $53 \pm 3 \mu\text{m}$   
 Colour: White

### GENERAL CHARACTERISTICS:

- High density and good transparency.
- Excellent resistance in die-cut pressure.

### CAUTION

- The Product must be stored in shady (or cool) places and must not be exposed to sunlight directly.
- All technical data above are based upon test results believed to be reliable in standard condition without guarantee or warranty totally. Customers have independently understood and determined the exact item among our range of products which suitable for each purpose.

