


VieTape SE3601

Polyester Film

The polyester film coated with one side silicone - adhesive, suitable for high temperature masking spray protection

PRODUCT FEATURES

- Strong adhesion.
- High temperature resistance.
- Chemical resistance, good insulation properties.
- No Adhesive residue when removed.



PERFORMANCE FEATURES

Physical Properties	Values	Testing Method
Color	Green	Sight-seeing
Backing Thickness	50 µm	ASTM D-3652
Total Thickness	80 µm	ASTM D-3652
Adhesion to Steel	9 N/25mm	ASTM D-3330
Tensile Strength	≥ 210 MPa (MD) ≥ 250 MPa (TD)	ASTM D-3759
Elongation	≥ 190% (MD) ≥ 130% (MD)	ASTM D-3759
Backing	Polyester Film	
Adhesive System	Silicone	

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. We assume no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (70 F to 80 F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants.

