



Technical Data Sheet

3M™ Venture Tape™ Double Coated PE Foam Glazing Tape VG1208



[Product Details](#)



[Regulatory Info/SDS](#)

Product Description

3M™ Venture Tape™ Double Coated PE Foam Glazing Tape VG1208 is 1/8" thick closed cell, crosslinked polyethylene foam tape coated on both sides with a high performance acrylic based pressure sensitive adhesive with a 4 mil blue poly liner.

Product Features

- Easily die cut.
- Low application temperature
- Great chemical resistance.
- Low compression set.
- Best conformability, cushioning and vibration damping.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Black, White
Adhesive Carrier		PE Foam
Density	ASTM D3574	40 kg/m ³ (2.5 lb/ft ³) ¹

¹ Foam with adhesive

Attribute Name	Test Method	Test Condition	Value
Total Tape Thickness	ASTM D3652		3.3 mm (129 mil)
Adhesive Thickness	PSTC-133	Faceside	0.051 mm (2 mil)
Adhesive Thickness	PSTC-133	Backside	0.051 mm (2 mil)
Carrier Thickness	PSTC-133		3.175 mm (125 mil)
Liner			4 mil Blue Poly

Typical Performance Characteristics

Attribute Name	Test Method	Value
Peel Adhesion	PSTC-101	22.2 N/25.4mm (80 oz/in)
Elongation	PSTC-131	210 %
Tensile Strength	PSTC-131	700 N/25.4mm (160 lb/in)
Tack	ASTM D2979	936 g (33 oz)

Shear Adhesion

Test Method: PSTC-107

Value
>24 h @ 15.2 kPa
>24 h ¹

¹ @2.2 psi

Attribute Name	Value
Minimum Application Temperature	10 °C (50 °F)
Long Term Temperature Resistance	82 °C (180 °F) ¹
Minimum Long Term Temperature Resistance	-12 °C (10 °F) ¹

¹ Long Term (day, weeks)

Storage and Shelf Life

24 months from date of manufacture when stored in original cartons at 70°F (21°C) and 50% relative humidity.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M
Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550

3M is a trademark of 3M Company.
©3M 2020 (3/20)