

## **Technical Data Sheet**

# VieTape 500DS-300

### Holding tape

0.03mm PET film with 0.025mm Rubber PSA rubber adhesive system

#### PRODUCT FEATURE

- It is a combination of PET film and Rubber PSA glue
- Heat resistance greater than 100°C
- Used to fix details and components in electronic equipment, household electrical appliances, refrigeration...
- It can be used as a PET cover to protect the surface from scratches...

#### PERFORMANCE FEATURES

Item	Parameter	Value
Product name	VieTape DS500-30	
Structure	PET film thickness	0.03mm
	Adhesive thickness	0.025mm ± 0.005mm
	Color	Clear
Features	Adhesive to steel 180°	From 600gf/25mm ± 10%
	Heat resistance	> 100°C
	Adhesive type	Acrylic PSA
	ROHS Compliances	Yes
Sizes	Standard width	960mm
	Standard length	35m
	Core size (D)	3 inches
	Special sizes	Width & Length following customers' request

#### **STORAGE CONDITION & SHELF LIFE**

- Within 6 months in normal room temperature.
- Never keep touching to the floor directly.

#### **IMPORTANT NOTICE**

- The above values are sample observed values, not the guarantee performance.
- Performance under actual usage conditions should be tested for the most accurate results for each application.

#### VIETAPE MATERIAL TECHNOLOGY CO., LTD



Adhesive thickness 0.025mm

PET film thickness 0.03mm