

# **FPA110-1FR**

## FLAME RETARDANT THERMOPLASTIC FILM ADHESIVE

## **KEY FEATURES**

- Excellent fire retardancy
- Easily removable during refurbishment
- Meets BMS 5-158 Type II product specification for the aerospace industry

#### **DESCRIPTION**

Bostik's FPA110-1FR is a fire retardant, thermoplastic film adhesive designed for use in the transportation industry. FPA110-1FR has excellent adhesion to PVF, vinyl, aluminum, polyamide film, phenolic prepreg and various fabrics and wools. The product can be used to bond decorative laminates to walls and furniture and can be removed easily during refurbishment.

## **FEATURES**

- Thermoplastic bonding film
- Heat activated at 220 to 235°F (104 to 113°C)
- · Heat resistance up to 200°F (93°C)

## **BENEFITS**

- Excellent fire retardant properties
- Removable sidewall bonding of PVF decorative during aircraft refurbishment
- · Can be bonded in a platen press or vacuum bag process

#### **BASIC USES**

- $\cdot \, \mathsf{Removable} \, \, \mathsf{decorative} \, \mathsf{laminates} \,$
- · Bonding PVF decoratives
- Textile bonding

# **DIRECTIONS FOR USE**

FPA110-1FR was designed as a mounting film for decorative laminates. The FPA110-1FR film can be tacked to the backside of the decorative at 220-235°F (104-113°C). The adhesive backed decorative can be vacuum bagged to the crushed core panel at the same temperature and 20-50 psi (138-345 kPa).

#### **PACKAGING**

FPA110-1FR is available at a 1 mil (25 microns) thickness, widths of 53 and 59 inches (135 and 150 cm), and a roll length of 500 ly (457 m).



TYPICAL PHYSICAL PROPERTIES	
Description	Results
Appearance	Off-white
Film Weight	32 g/m²
Density of Film @ 25°C	1.6 g/cm³ (13.3 lb/gal)
SAFT Heat Resistance	200°F (93°C)
AVAILABILITY	
Film Thickness	1.0 mils (25 microns)
Width	53 and 59 in (135 and 150 cm)
Length	Up to 500 ly (457 m)
ID Core Size	3 in (7.6 cm)

#### **SHELF LIFE**

Store in a dry location at  $40 \text{ to } 80^{\circ}\text{F}$  ( $4 \text{ to } 27^{\circ}\text{C}$ ). Shelf life is approximately 24 months under these conditions.

#### **FURTHER INFORMATION**

Please refer to SDS for complete details.

#### **LIMITED WARRANTY**

Limited Warranty found at www.bostik-us.com or call 800-726-7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

