




tesa® 60537

Product Information



30µm single sided electrically conductive copper tape

Product Description

tesa® 60537 is a single sided electrically conductive self adhesive tape. It consists of an electrically conductive copper backing and an electrically conductive acrylic adhesive. Designed for EMI shielding and ESD grounding for display and other components applications.

Product Features

- Excellent EMI shielding performance
- Excellent electrical conductivity in XYZ-direction for very good grounding performance
- High adhesion level and very good anti-repulsion performance

Application Fields

- EMI shielding and grounding applications
- Electrostatic discharge applications
- FPC shielding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	copper film	• Color	orange
• Type of adhesive	conductive acrylic	• Color of liner	transparent
• Type of liner	PET	• Thickness of liner	50 µm
• Total thickness	30 µm		

Properties/Performance Values

• Contact resistance z-direction (initial)	0.05 Ohm / square inch	• Surface resistance x-y-direction	0.2 mOhm
• Release of liner	easy	• Temperature resistance short term	200 °C
• Static shear resistance at 40°C	good		

Adhesion to Values

- Steel (after 14 days) 7.5 N/cm



tesa[®] 60537

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60537>