

3M™ Temflex™ Vinyl Electrical Tape 150

Technical Data

May/2023

Product Description

3M™ Temflex™ Vinyl Electrical Tape 150 is an economical general-purpose grade, nominal 0.13 mm thick electrical insulating tape composed of an elastic vinyl (PVC) film backing coated on one side with a non-corrosive, pressure-sensitive adhesive. Available in 9 colors.

Commonly used in these types of applications:

- For residential, commercial and manufacturing (OEM) environments
- Suitable for ambient indoor uses
- General wire harness taping, bundling wires, cables and wire pulling and fishing
- Basic electrical and hardware applications

Typical Properties

Physical Properties	Typical Value ¹ Imperial (Metric)	Mechanical Properties	Typical Value ¹ Imperial (Metric)
Color-Visual	Black, Blue, Red, Yellow, White, Orange, Brown, Green, Grey	Thickness ³	0.13mm±10%
Adhesive	Rubber-based	Adhesion to steel ³	20oz/in (0.22N/mm)
Backing	Vinyl (PVC)	Adhesion to backing ³	20oz/in (0.22N/mm)
Flame Retardant ²	Pass	Tensile Strength ³	2500psi
Electrical Properties	Typical Value ¹ Imperial (Metric)	Elongation ³	200%
Dielectric Strength ²	1.2kV/mil		

Notes:

1. Not for specification. Values are typical, not to be considered minimum or maximum.
2. Flame retardant test method refers to UL510
3. ASTM D1000 Test Method-properties measured at room temperature 23°C unless otherwise stated.

Agency Approval & Self Certifications

- For Regulatory information including RoHS, REACH, please visit www.3M.com/regs

Installation Techniques

3M Temflex™ Vinyl Electrical Tape 150 shall be applied in half-lapped layers with sufficient tension to produce a uniform wind. On pigtail splices, the tape shall be wrapped beyond the end of the wires and then folded back, leaving a protective cushion to resist cut-through. Wrap tape up-hill, taping from a smaller diameter surface to a larger diameter surface. Apply the tape with no tension on the last wrap to prevent flagging.

Shelf Life & Storage

This product has a 2-year shelf life (from date of manufacture) when stored in humidity-controlled storage (10°C-27°C and <75% relative humidity)

3M™ Temflex™ Vinyl Electrical Tape 150

TECHNICAL STATEMENT

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com

3M and Temflex are trademarks of 3M Company.



Electrical Markets Division

13011 McCallen Pass, Bldg. C

Austin, TX 78753

Phone: 800.245.3573

www.3M.com/electrical