

Technical Data Sheet

Electronic & Engineering materials

CONAP S-13

Conformal Coating Reducing Solvent

ELANTAS Malaysia Sdn. Bhd.

Lot 550, Jalan Keretapi Lama,
Batu 7 ½, Jalan Kapar/KU15,
42200 Kapar
Selangor Darul Ehsan, Malaysia

www.elantas.com

Product Description

CONAP S-13 is aromatic hydrocarbon solvent.

Areas of Application

Viscosity adjuster for CONATHANE® CE-1170

Features and Benefits

Maintains proper relationship between solids and viscosity.

Instructions for Use

CONAP S-13 should be added at room temperature to adjust resin viscosity or to compensate for evaporative losses.

It can also be used as a clean up solvent.

Transportation / Storage

Store at or below 25°C / 77°F in a dry controlled environment out of direct sunlight. This material should be suitable for use stored under these conditions in the original sealed containers for twelve (12) months from the date of shipment.

Keep containers tightly sealed to minimize evaporation.

Failure to store the product as recommended above may lead to deterioration in product performance.

Health / Safety

Refer to the Safety Data Sheet.

Typical Properties of Material as Supplied

Property	Conditions	Value
Color	25°C / 77°F	Water White
Specific Gravity @25°C, kg/L	20°C / 68°F	0.85-0.88

This information is presented in good faith to assist the customer in determining whether our products are suitable for his application. No Warranty or representation, however, is intended or made, nor is protection from any law or patent to be inferred and all patent rights are reserved.